
ESD MANUAL WORKSTATION
L-TYPE 1200 MM




*Table with full equipment -
option to expand with additional accessories

AVAILABLE TABLETOP TYPES



RECTANGULAR TABLETOP



ERGONOMIC TABLETOP

AVAILABLE MODELS
(by dimensions)



RT-L/M/ESD/120/70

RT-L/M/ESD/120/70/E

1200 x 700 MM



RT-L/M/ESD/120/80

RT-L/M/ESD/120/80/E

1200 x 800 MM



RT-L/M/ESD/120/90

RT-L/M/ESD/120/90/E

1200 x 900 MM

+48 518 633 620

export@rtwork.pl | info@robtools.pl

www.rtwork-esd.com | www.robtools.pl

ESD MANUAL WORKSTATION L-TYPE 1200 MM

Rectangular tabletop	**RT-L/M/ESD/120/70**	**RT-L/M/ESD/120/80**	**RT-L/M/ESD/120/90**
Ergonomic tabletop	**RT-L/M/ESD/120/70/E**	**RT-L/M/ESD/120/80/E**	**RT-L/M/ESD/120/90/E**

Type of height adjustment (mm)	MANUAL 50 MM STEP		
Height adjustment range (mm)	750 - 1100		
Width (mm)	1200		
Depth (mm)	700	800	900
Weight (kg)	44	47	50
Max load (kg)	300		
Profile dimensions (mm)	40 x 40 x 1,5 | 60 x 40 x 1,5		
Sheet thickness bottom panel (mm)	1,50		
Sheet thickness tabletop fixing (mm)	1,50		
Sheet thickness vertical upright fixing (mm)	2,00		
Color	RAL 7035 (LIGHT GREY) | RAL 9005 (BLACK)		
Material of table frame	CONSTRUCTION STEEL		
Tabletop	DOUBLE SIDED ANTISTATIC, DISSIPATIVE, WITH GRAPHITE ADDITIVE, COVERED WITH A MELAMINE LAYER, THICKNESS 25 mm		
Possibility to choosing accessories	YES		
Type of glides	SELF-LEVELLING		
Resistance tabletop - grounding (Ohm)	$10^4 – 10^8$		
Resistance table frame (Ohm)	$10^4 – 10^8$		
Compliance with standards	ANSI/ESD S.20.20.2021, PN-EN 61340-5-1:2024, PN-EN ISO 9001:2015, PN-EN ISO 3834-2:2021, PN-EN 1090-1:2009+A1:2011		

+48 518 633 620 | export@rtwork.pl | info@robtools.pl | www.rtwork-esd.com | www.robtools.pl